



# General-Purpose Scraper

## *Model 5520*



**For the many chores around the farm, ranch, or job site!**

**Buffalo General-Purpose Scrapers** are built for those various jobs around the home, farm, ranch, or construction job site. Available in 10' and 12' sizes, these versatile, ruggedly constructed scrapers are designed to provide the operator years of trouble-free service.

**Standard features** include 11L-15 8-ply tires; clevis hitch; 6-bolt, 3,560-pound hub and spindle; and adjustable-tilt axle.

**Optional features** include 3" cylinder and hoses for the adjustable-tilt axle and lift arm.

### **Outstanding Features!**

- 10' and 12' widths
- Standard adjustable-tilt axle
- Standard clevis hitch
- 12" dump height
- Optional sight gauge enables operator to judge when scraper is level
- New ribbed 11L-15 implement tires are standard
- 6-bolt, 3,560-pound hubs

## Specifications for General-Purpose Scrapers

Model Number	55200010	55200012
Width of Cut	10'	12'
Capacity (heaped)	2.5 cu yd	3 cu yd
Maximum Dump Height	12"	12"
Weight (lbs)	1,800	2,100
Overall Width	10' 1"	12' 1"
Overall Length	12' 6"	12' 6"
Overall Height	44"	44"
Adjustable Tilt Axle	Standard	Standard
Horsepower Requirements (min/max)	100-125 HP	125-150 HP
Hitch	Clevis	Clevis
Cylinders:		
Lift	One 3" x 8" (optional)	
Tilt Axle	One 3" x 8" (optional)	
Side Plates	1/4"	1/4"
Cutting Blade	1/2" x 6" x	
Qty / Length	Two 5'	Two 6'
Tire Size	11L x 15 8-ply	11L x 15 8-ply
Hub & Spindle	6-Bolt, 3,560-lb	6-Bolt, 3,560-lb
Sight Gauge	Optional	Optional

*Specifications and design subject to change without notice*



*Standard adjustable-tilt axle allows precise depth control on either side of the scraper*

### Adjustable-Tilt Axle

**Buffalo General-Purpose Scrapers** offer as standard equipment an adjustable-tilt axle. This unique feature gives the operator broad flexibility in cutting depths on either side. This feature is ideal for shaping lots, crowning driveways for better water runoff, cutting ditches, and a host of other uses.

The adjustable tilt axle can be operated with the ratchet jack from the lift arm, or with an optional 3-inch cylinder.



*The adjustable-tilt axle can vary the cutting depth left or right*

Buffalo offers a full line of scraper models and sizes. See your dealer for details.



### Henke Machine • Buffalo Equipment

1001 East Eisenhower Avenue, P.O. Box 1248, Norfolk, NE 68702-1248  
Phone: 402-371-1400 • Toll-Free: 800-228-1405 • Fax: 402-379-0429